

RP 120V

LAMP TYPE: G9 base — Maximum 5 Watts LED
FOR OUTDOOR USE ONLY • SUITABLE FOR WET LOCATIONS

WARNING — Risk of Electric Shock. Verify that power is OFF before installing this fixture. This fixture must be installed in accordance with the National Electric Code and/or local codes. Failure to do so may result in serious personal injury or death. Wiring must be done by a licensed electrician.

INSTALLATION — WOOD SURFACE

1. Place Mounting Collar in desired position and mark the mounting and conduit holes. Drill pilot holes for mounting screws and for conduit or wireway as applicable.
2. Run conduit/wires to fixture location, making sure the wires extend at least 6 inches past the top of the Collar.
3. Fasten Collar into position with the three supplied lag screws.
4. Join fixture leads to the supply wires with silicone-filled wire nuts (supplied) as shown in the diagram: black lead connects to hot, white to neutral, and green to ground. Use silicone or electrical tape around wire nuts to ensure proper connection.
5. Slide the fixture Base over the Collar. Rotate to desired position and use a 5/32" hex wrench to tighten the three set screws to fasten the Base to the Collar.

INSTALLATION — MASONRY

1. Dig a minimum 8" diameter x 8" deep hole at desired fixture location. Alternately, an 8"x8"x8" concrete block can be used as a form for the poured concrete.
2. Use the Mounting Collar as a template to position the conduit so it fits inside the footprint of the Base and extend approximately 1/4" above grade.
3. With conduit in place, fill the hole (or concrete block) with concrete.
4. After the concrete has cured, drill three holes for the masonry anchors using the Internal Collar as a template. Install anchors.
5. Proceed to Step 2 of Installation — Wood Surface above to complete installation.

LAMPING

1. Use a 5/64" hex wrench to loosen—but not remove—the set screws in the Top that engage the four Posts. Lift the Top off the Posts.
2. Turn the Lamp Compartment counterclockwise. It will unscrew at its base. The Glass and Cap are permanently attached to the Housing; do not attempt to separate these pieces.
3. Grasp the lamp with a soft cloth and pull straight up to remove from socket.
4. Align the pins of the new lamp with the holes in the socket and push the lamp straight down into the socket.
5. Replace the Lamp Compartment, threading it completely down onto the gasket.
6. Reposition the Top over the four Posts, making sure each one is fully inserted into its recess in the underside of the Top, and tighten the set screws in the side of the Top to secure.



