

# 2W-A / 2W-RO

2-Watt Amber or Red-Orange LED modules certified by Florida Fish and Wildlife Conservation Commission as 'Wildlife Friendly'.



**Wildlife Lighting  
Certification Number  
2018-029**



**Construction** Anodized aluminum cylindrical body. For use in enclosed fixtures.

**Voltage** 12 Volts LED. Integral driver operates on 9-15 Volts AC input. Remote transformer required


**Mounting** Standard 1/8 IPS (lamp part size) female thread 1/4" deep [6.4 mm]

**Lamp** Single Cree XPE-2, AMBER (1600K) or RED-ORANGE (1000K)


— <b>2W-A-SP</b>	— <b>2W-RO-SP</b>	10° spot
— <b>2W-A-NFL</b> (98 lm)	— <b>2W-RO-NFL</b> (107 lm)	30° narrow flood
— <b>2W-A-FL</b>	— <b>2W-RO-FL</b>	50° flood
— <b>2W-A-NO</b>	— <b>2W-RO-NO</b>	No Optic

**Wavelength** 2W-A: 590 nanometers dominant, 595 nm peak  
2W-RO: 612 nanometers dominant, 623.53 nm peak

**L70** 40,000 hours



Ø1.36"  
[Ø34.5mm]



1.57"  
[40.0mm]

1/8 IPS

5-year warranty when used in completely sealed fixture  
ETL/Interek #3188461

Project _____	By _____	Date _____
For ordering purposes, please specify (example: <b>2W-A-SP</b> )		
<b>2W-</b> _____	— _____	Optic _____