

2W-RO

2-Watt Red-Orange LED module approved by Florida Fish and Wildlife Conservation Commission as 'Wildlife Friendly'.



Construction Anodized aluminum cylindrical body. For use in enclosed fixtures.

Voltage 12 Volts LED. Integral driver operates on 9-15 Volts AC input. Remote transformer required


Mounting Standard 1/8 IPS (lamp part size) female thread 1/4" deep [6.4 mm]

Lamp Single Cree XPE-2, 1000K


— 2W-RO-SP	10° spot	
— 2W-RO-NFL	30° narrow flood	107 lm
— 2W-RO-FL	50° flood	
— 2W-RO-NO	No Optic	

Wavelength 612 nanometers dominant, 623.53 nm peak

L70 40,000 hours



Ø1.36"
[Ø34.5mm]



1.57"
[40.0mm]

1/8 IPS

Project _____	By _____	Date _____						
For ordering purposes, please specify (example: 2W-RO-SP)								
<table style="margin: auto; border: none;"> <tr> <td style="text-align: center;">2W-RO</td> <td style="text-align: center;">—</td> <td style="text-align: center;">_____</td> </tr> <tr> <td></td> <td style="text-align: center;">Optic</td> <td></td> </tr> </table>			2W-RO	—	_____		Optic	
2W-RO	—	_____						
	Optic							