.-009

The -009 is a low-voltage, in-grade, brass uplighting fixture.

Construction All brass components. 0.140" [3.6mm] thick brass housing.

Lens Tempered glass, stepped to prevent pooling of water on lens.


- Voltage 12 Volts AC. Remote magnetic transformer required.
- Lamps GU5.3 MR16 LED Amber (1500K), Warm White (2700K/3000K) Most lamps dim to less than 20%. See lamp manufacturer's transformer/dimmer compatibility chart.


5 Watt Cree chipset	5W-A-NFL	AMBER (1500K)	25° narrow flood	83 lm	
	<u>2700K</u>	<u>3000K</u>			
Cree chipset 5 Watts	5W-SP-27 5W-NFL-27 5W-FL-27 5W-FL/60-27 5W-WFL-27	5W-SP-30 5W-NFL-30 5W-FL-30 5W-FL/60-30 5W-WFL-30	15° spot 25° narrow flood 40° flood 60° flood 100° wide flood	320 lm 320 lm 320 lm 320 lm 320 lm	85+ CRI 85+ CRI 85+ CRI 85+ CRI 85+ CRI
Lumiled chipset 7 Watts	7W-FL/60-27	7W-FL/60-30	60° flood	483 lm	90+ CRI
Soraa chipset 8 Watts	8W-SP-27 8W-NFL-27 8W-FL-27	8W-SP-30 8W-NFL-30 8W-FL-30	10° spot 25° narrow flood 36° flood	600 lm 630 lm 630 lm	90 CRI 90 CRI 90 CRI

AccessoriesBGS9 FR		Brass glare shield Frosted lens
	HL2	Honeycomb louver, 1/4" [6mm] thick (1/8" [3mm] thick honeycomb louver is standard)
	PR	Prismatic spread lens
	RT	Rectilinear spread lens
	SL	Solite soft focus lens

Finish: Unfinished is standard; no specification required. The fixture will weather to a natural patina. The patina process is natural with brass and copper. Rate of patina and eventual color is dependent upon climate and proximity to the ocean. Thus, Beachside does not guarantee any specific appearance.







BRASS HOUSING AND COMPONENTS

Weight: 5.2 lbs / 2.4 kg

IP66

10 year fixture warranty 3 year warranty on MR16 LED lamps



