

L-016-SQ



Wildlife Lighting
Certification Number
2018-029

The L-016-SQ recessed fixture combines the flexibility of a standard MR16 lamp with the corrosion resistance expected of a Beachside fixture. The gasket on the brass trim securely seals up against the bottom of the recessed, stainless steel can and the frame is powder-coated steel. An internal brass bracket allows 360° rotation and angling up to 28° without an optical accessory (no beam cutoff up to 26° with 36° flood lamp) or 10° with. The L-016-SQ is intended for new construction applications and features an integral **magnetic transformer** (120V primary, 12V secondary). The "-SQ" designation denotes the square trim versus the round trims of the L-016 and L-016-F.

Housing Recessed ceiling fixture for new construction.

Mounting Lamp housing is removable through ceiling aperture for access to junction box. Housing can be lowered and adjusted to ceiling thickness. Dual extension hanger bars span from 15" (38.1 cm) to 25-1/4" (64.1 cm) with reversible placement feature. Bars attach to sides along length or width of mounting frame. Hanger bars may be extended to rest on T-bar grid. For insulated ceilings, maintain a minimum 3" clearance around fixture.

Electrical Magnetic, Class H transformer with Molex disconnect in j-box is fully dimmable with magnetic low voltage dimmers. Transformer has internal thermal protection. J-box has (4) 1/2" K.O.'s and (2) concentric 1/2" x 3/4" K.O.'s with spring latch access plates. Suitable for Wet Location Use.

Lenses Tempered soda lime glass.

☐ **CL** Clear ☐ **FR** Frosted

Lamps MR16 LED • GU5.3

Cree chipset
AMBER (1500K) ☐ **5W-A-NFL** 5 Watt 25° narrow flood 83 lm

Cree XPG3 triple-LED light engines

Cree XPG3 triple LED
AMBER (1500K) ☐ **7W-A-FL** 7 Watt 66° Beam, 109° Field 61 lm 48 cd
☐ **7W-A-NFL** 7 Watt 28° Beam, 49° Field 98 lm 346 cd

Red-Orange (1000K) ☐ **10W-RO-NFL** 10 Watt 27° Beam, 43° Field 212 lm 884 cd
☐ **10W-RO-FL** 10 Watt 51° Beam, 78° Field 192 lm 254 cd

Accessories Lamp-attached For light engines




(only one available) ☐ **FR-MR16** ☐ **FR-LBTZ** Frosted lens
☐ **HL-MR16** ☐ **HL-LBTZ** Honeycomb louver, 1/8" [3mm] thick
☐ **PR-MR16** ☐ **PR-LBTZ** Prismatic spread lens
☐ **RT-MR16** ☐ **RT-LBTZ** Rectilinear spread lens
☐ **SL-MR16** ☐ **SL-LBTZ** Solite (soft focus) lens

Finish ☐ **FIN-BK** Black Acid Finish
☐ **FIN-DB** Dark Bronze Acid Finish
☐ **FIN-NA** Nickel Acid Finish
☐ **FIN-WH** White Powder Coating

Unfinished is standard—no specification required. The fixture will weather to a natural patina. The patina process is natural with brass and copper. Rate of patina and eventual color is dependent upon climate and proximity to the ocean. Thus, Beachside does not guarantee any specific appearance.

Weight: 7 lbs [3.2 kg]

IP 66
 CSA Listed, file #190030
 10 year fixture warranty
 3 year LED module warranty
 3 year warranty of MR16 LED lamps



**SUITABLE FOR
 INDOOR USE UP
 TO 12W LED**

Project		By		Date	
For ordering purposes, please specify (example: L-016-SQ—CL—5W-A-NFL—HL-MR16—FIN-BK)					
L-016-SQ	—	—	—	—	—
Fixture	Lens	Lamp	Accessory	Finish (if any)	