

MB2

The MB2 is a classic-style bollard for concrete installation. MB-series bollards set the standard for durable, corrosion-resistant walkway lighting.

Construction All brass components. 4" diameter brass tube x 0.090" wall thickness. (102 mm x 2.3 mm)

Mounting Concrete-mounted fixture uses 3/8" stainless steel anchor bolts through an internal brass mounting collar. Stainless steel hex nuts and washers below collar allow for leveling.

Electrical 12/120/230 Volt LED — Driver is integral to lamp
120/230/277 Volt for Metal Halide

Lens Clear Borosilicate glass, 5 mm wall thickness.

Voltage / Lamp Options

12V MR16 LED • GU5.3 • Remote transformer required

- **5W-A-NFL** 5 Watt **AMBER** (1500K)
- **5W-NFL** 5 Watt Warm White (3000K)
- **7W-NFL** 7 Watt Warm White (3000K)
- **8W-NFL** 8 Watt Warm White (3000K)

Triple LED Module • Remote transformer required
Triac dimmable: MLV >1% typ., ELV >5% typ.

- **7W-A-SP** 7 Watt **AMBER** (1500K)
- **11W-SP** 11 Watt Warm White (3000K)*

* Also available in 2700K. Add color suffix to lamp specification, e.g. "11W-SP-2700K"

120 / 230V MR16 LED • GU10

- **5W-A-NFL** 5 Watt **AMBER** (1500K)
- **8W-NFL** 8 Watt Warm White (3000K) 42 cd 132 lm

120/230/277V MR16 Ceramic Metal Halide • GX10

- **MH20MR16SP** 20 Watt CMH (3000K) 87 cd 269 lm
- **MH39MR16SP** 39 Watt CMH (3000K) 150 cd 463 lm

Optical Accessory — **HS-MB2** Half-Shield for 180° illumination




Finish Unfinished is standard, no specification required.

- **FIN-BK** Black Acid Finish
- **FIN-DB** Dark Bronze Acid Finish
- **FIN-NK** Satin Nickel Plating

The fixture will weather to a natural patina. The patina process is natural with brass and copper. Rate of patina and eventual color is dependent upon climate and proximity to the ocean. Thus, Beachside does not guarantee any specific appearance.

Weight: 15 lbs / 6.8 kg

IP66
CSA Listed, file # 190030
10 year fixture warranty
3 year warranty on MR16 LED lamps



MB2 - Horizontal Footcandles at Radius from Fixture Base

Lamp	1' / 0.3m	2' / 0.6m	3' / 0.9m	4' / 1.2m	5' / 1.5m	6' / 1.8m	7' / 2.1m	8' / 2.4m	9' / 2.7m	10' / 3.0m
5W-A	0.43	0.91	0.54	0.29	0.16	0.09	0.05	0.03	0.02	0.01
8W	2.66	6.83	5.12	2.62	1.43	0.84	0.53	0.36	0.24	0.20

Project	By	Date
For ordering purposes, please specify (example: MB2—12V—5W-A—HS-MB2—FIN-DB)		
MB2	—	—
Fixture	Voltage	Lamp
—	—	—
Accessory	Finish (if any)	—