

## Wildlife Lighting **Certification Number** #2019-231

The MB4 is a contemporary brass bollard ideal for higher-traffic applications as an alternative to path light fixtures with shades.

Construction All brass components, including 5/32" [4 mm] thick brass

cylinder.

Clear borosilicate glass, 0.19" (4.8mm) wall thickness Lens

9" nominal (8.7" [22.0 cm] actual) **Overall Height** 

> \_\_ 20 20" [50.8 cm]

12V Lamps GU5.3 • MR16 LED • Remote transformer required

\_\_\_ **5W-A-NFL** 5 Watt **AMBER** (1500K) Cree chipset

Triple LED Module • Remote transformer required

Cree chipset Triac Dimmable >3%

7 Watt **AMBER** (1560K) 7W-A-SP 10 cd 35 lm

120V Lamps GU10 • MR16 LED

Cree chipset \_\_ **5W-A-NFL** 5 Watt **AMBER** (1500K)

Optical Accessory

Comes stock with **HS-MB4-270** for 90° illumination

Mounting **Accessories**  Comes stock with 1/2" male threads

BSB Brass Surface Box for surface-mount applications on concrete or wood. Includes

internal brass collar and stainless steel lag screws. 4.25" (11cm) diameter x 2.0" (5cm)

Heavy-duty Ground Spike with cast Brass \_GS2BC Cap (For 9" fixture height only. Not recom-

mended for 20" fixture.)

Cast brass Junction Box for recessed con-\_JB crete application. JB Cover remains above

grade.

Finish: Unfinished is standard; no specification required. The fixture will weather to a natural patina. The patina process is natural with brass and copper. Rate of patina and eventual color is dependent upon climate and proximity to the ocean. Thus, Beachside does not guarantee any specific appearance.

Weight: 3.4 lbs / 1.5 kg (9" height) 8.4 lbs / 3.8 kg (20" height)

IP66 10 year fixture warranty 3 year warranty on MR16 LED lamps

MB4

Fixture



Height



20.0" [50.8cm] Ø2.4" [6.1cm] 8 7 [22.0cm] 2.0" BSB [5.0cm] JB. Ø4.2" [10.6cm]

MB4-20

on JB

Lamp

Project Ву Date For ordering purposes, please specify (example: MB4-20-12V-7W-A-SP-HS-MB4-270-BSB) HS-MB4-270-

**MB4-9** 

BEACHSIDE LIGHTING • 800-405-6732 • www.BeachsideLighting.com • Made in Hawaii, USA

Voltage

**MB4-20** 

on BSB

Accessory(ies)